

INDOOR DIGITAL SIGNAGE

LARGE SIZE FORMAT APPLIED SCREEN

CLASS	MODEL
32"	D32AM

KEY FEATURES

- LED BLU, Slim Design
- Power Consumption Reduced at 40% Compared to Normal Display
- Built in Video Wall Function
- Portrait / Landscape Orientation
- High Connectivity
- Remote Control (RS232)



Broadcast your branding with Hyundai Digital Signage!

Thanks to the advanced product design, Hyundai Digital Signage Display meets requirements for various digital signage solutions. Not only take advantage from slim and simple design, but also think more about our future environment, saving energy up to 40 percent. LED technologies bring more than just expected.



SPECIFICATIONS

Model	D32AM	
Panel	Screen Size (diagonal)	32"
	Active Display Area (in/mm)	27.50 x 15.47 / 698.4 x 392.9
	Resolution	1920 x 1080
	Aspect Ratio	16:9
	Display Colors	16.7 M
	Brightness (cd/m²; typ.)	360
	Contrast Ratio	3000:1
	Response Time (ms; GTG)	8
	Viewing Angle	178°/178°
	Lifetime (hours)	50,000
	Backlight type	LED
Resolution	Monitor	1920 x 1080
	DTV	1080p
Input		VGA(D-Sub), HDMI DVI IR PC Audio RS232C
Output		DVI IR RS232C Audio Line Out Speaker (Ready)
Power	Input Voltage	100 – 240V AC
	Power consumption	60 W
Features	Fanless	yes
	Auto Power Control(DPMS)	yes
Operation	Temperature (°C)	0 - 40
	Humidity (%)	20 - 80
	OSD Language	10 Lang
Dimension	Set (W x H x D), in/mm	29.3 x 17.27 x 1.71 / 744.1 x 438.6 x 43.5
Bezel Size (U/D/L/R), in mm		0.82/0.82/0.82/0.82 21.1/21.1/21.1/21.1
Wall Mounting (WxH) mm		300 x 300
Weight	Set (kg)	24.25 / 11

FEATURES

LED Backlight

HYUNDAI's public displays with LED backlight bring the advantage of up to 40% lower power consumption, compared to displays with CCFL backlight.

Easy operating OSD menu, Remote control



In order to setup a multi display wall, the single units are linked by a daisy chain connection over DVI interface. The configuration of each display can be easily set-up over the on-screen menu or the RS232C interface.

Slim Design

These products enable the slim design.

DIMENSIONS

D32AM [unit: mm]



Specifications and design are subject to change without notice. See our website for detailed information.

UPDATE: OCT. 2013

HEAD OFFICE - HYUNDAI IBT CO., LTD.

106, Apogongdan-gil, Gimche on-si, Gyeongsangbuk-do,
740-862 The Republic of Korea
Tel. +82 54 430 6426 E-mail: prio123@hyundaiibt.com
www.hyundaiibt.com

HYUNDAI IT AMERICA CORP.

2051 Junction AVE., Suite 112 San Jose, CA 95131, USA
Tel. +1 408 954 8920 email : sales@hyundaita.com
www.hyundaita.com

HYUNDAI IT EUROPE GMBH

Siemensstrasse 22, 63225 Langen, Germany
Tel. +49(0) 6103-38878-100 email : info@hyundaiit.eu
www.hyundaiit.eu

HYUNDAI IT JAPAN

Kawaziri Bldg 2F, 534 Waseda Tsurumakicho,
Shinjuku-ku, Tokyo, Japan
Tel. +81-3-6273-9652 email : sales@hyundaiit.co.jp
www.hyundaiit.com